

Specifications and Features:

Radiant™ LED

- Conformal Coating LED light engine
- CCT: Amber, LPS (1800K), 2200K, 2700K, 3000K, 4000K, 5000K
- Static Colors Available - Contact Factory

Distribution

- Types I* II, III, IV, V (Type I available in 70w & higher only)

Electrical

- Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz
- 0-10v Dimmable Driver
- Standard Surge Protection included (6kV line-line; 10k-V line-earth)

Controls (Optional)

- Button eye photo control (PC)
- House Side Shield (H)
- 7-pin twist-lock receptacle (PCR7)*
- 3-pin twist-lock receptacle (PCR3)*

*C10 Capital Required for PCR7 & PCR3

Housing

- Decorative aluminum capital housing choices with 3" slip fitter

Finish

- Super durable polyester powder coat finish. Custom finishes available, including patinas and all RAL colors.

Listings & Ratings

- ETL listed to UL 1598 standard for wet location.
- LED is IP66 Rated

Warranty

- 5 year limited warranty



EPA: 2.9
WEIGHT: 42 lbs (max.)

Order Information Example:

LON2FGC1070W4KU5NBPCBK

LON2		C10			
Model	Globe/Lens	Capital	LED Module	Voltage	Distribution
LON2=London 2 Radiant	CA=Clear Acrylic, CP=Clear Polycarbonate FP=Frosted Polycarbonate, TG=Flat Tempered Glass, Clear, FG=Flat Tempered Glass, Frosted, WA=White (Opal) Acrylic, PA=Pattern Acrylic	C10=PLC10	See Chart on Page 2	U=120-277V H=347/480V	1=Type I* 2=Type II 3=Type III 4=Type IV 5=Type V *70W & above only
Mounting	Finial	Options		Finish	
N=Post Mount (Standard) PEN=Pendant Mount WM=Wall Mount	H=GF8 (standard), B=GF2, C=GF3, D=GF4, F=GF6, G=GF7, I=GF9, J=GF10, K=GF12, O=GF17, P=GF18, V=GF24 N=None	PC=Button Eye Photo Control H=House Side Shield PCR3=3 Pin Twist Lock Receptacle (photo cell not included)* PCR7=7 Pin Twist Lock Receptacle (photo cell not included)* N=None *Must use C10 Capital		BK=Black BZ=Bronze DBZ=Dark Bronze WH=White GR=Green SM=Silver Metallic GY=Light Gray TBK=Textured Black CC=Custom Color (Consult Factory)	

London 2 LED Post Top



12" Radiant™



8" Radiant™

Lumen Output for London 1 & 2

Clear Acrylic Lens

CCT	LED Module	Input Watts	Type 2	Type 3	Type 4	Type 5	CCT	LED Module	Input Watts	Type 2	Type 3	Type 4	Type 5
5K	40W5K	40	4429	4437	4285	4526	3K	40W3K	40	4119	4126	3985	4209
	50W5K	50	5491	5493	5286	5539		50W3K	50	5106	5109	4916	5152
	60W5K	60	6100	5989	5878	6265		60W3K	60	5673	5570	5466	5826
	70W5K	70	6318	6451	6335	6710		70W3K	70	5876	6000	5892	6241
	80W5K	80	7221	7372	7240	7669		80W3K	80	6715	6856	6733	7132
	90W5K	90	8123	8294	8145	8628	90W3K	90	7555	7713	7575	8024	
4K	40W5K	40	4274	4282	4135	4367	27K	40W27K	40	4037	4044	3905	4125
	50W4K	50	5298	5301	5101	5345		50W27K	50	5004	5006	4818	5049
	60W4K	60	5887	5779	5672	6046		60W27K	60	5560	5458	5357	5710
	70W4K	70	6097	6225	6113	6475		70W27K	70	5758	5880	5774	6116
	80W4K	80	6968	7114	6986	7400		80W27K	80	6581	6719	6598	6990
	90W4K	90	7839	8003	7860	8326		90W27K	90	7403	7559	7423	7863

****15% LLF for Frosted Lens****

****20% LLF for White/Opal Lens****

Contact the factory for Amber, LPS, 2200K Lumen Output

Finials



GF2 - 6"



GF3 - 6"



GF4 - 6"



GF6 - 4"



GF7 - 4.5"



GF8 - 4"



GF9 - 4.25"



GF10 - 3.5"



GF12 - 2.75"



GF17 - 4"



GF18 - 2.75"



GF24 - 4.75"

