



SRT2 with C1 Capital, A1 Cage, T3 Top Spinning and no finial

EPA: 2.2
WEIGHT: 32 lbs (max.)



Quick Ship
Options in **RED**

Specifications and Features:

Opti-FLUX™ LED

- CCT: 2700, 3000, 4000, 5000

Distribution

- Types III & V

Electrical

- Electronic 0-10V Dimmable Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz
- Standard Surge Protection included (6kV line-line; 10k-V line-earth)

Controls (Optional)

- Button eye photo control (PC)
- House Side Shield (H)
- 7-pin twist-lock receptacle (PCR7)**
- 3-pin twist-lock receptacle (PCR3)**

Housing

- Decorative capital housing choices with 3" slip fitter*

Finish

- Super durable polyester powder coat finish. Custom finishes available, including patinas and all RAL colors.

Listings & Ratings

- ETL listed to UL 1598 standard for wet location

Warranty

- 5 year limited warranty

Order Information Example:

SRT2PAC856W4KU3A1T1NFBK

SRT2

Model	Globe/Lens	Capital	LED Module	Voltage	Distribution
SRT2=Saratoga 2 Prismatic Globe Post Top	PA=Prismatic Acrylic PP=Prismatic Polycarbonate	C1=PLC1, C2=PLC2, C3=PLC3, C4=PLC4, C5=PLC5, C6=PLC6 C7=PLC7, C8=PLC8, C9=PLC9, C10=PLC10, C11=PLC11	See Chart on Page 2 & 3	U=120-277V H=347/480V	3=Type III 5=Type V
Bands & Cages	Spinning	Options	Finial	Finish	
A1=DECA1 A2=DECA2 A3=DECA3 A6=Perforated Band w/Cage A7=Flat Band w/Cage N=None	T1=T101 T3=T103 T4=T104 N=None	PC=Button Eye Photo Control H=House Side Shield PCR3=3 Pin Twist Lock Receptable (photo cell not included)* PCR7=7 Pin Twist Lock Receptable (photo cell not included)* N=None *C8, C10 Capital Only	B=GF2, C=GF3, D=GF4, E=GF5*, F=GF6, G=GF7, H=GF8, I=GF9, J=GF10, K=GF12, O=GF17, P=GF18, V=GF24 N=None *Black finish only	BK=Black BZ=Bronze DBZ=Dark Bronze WH=White GR=Green SM=Silver Metallic GY=Light Gray TBK=Textured Black CC=Custom Color (Consult Factory)	

Saratoga 2

LED Post Top



Opti-FLUX™ LED
Light Engine

Lumen Output for SRT2										
	Input Watts	LED Module	Efficacy Range		Type 3			Type 5		
					Solid Top	Light Lid	Perf Lid	Solid Top	Light Lid	Perf Lid
5K	37	32W5K	103	115	3862	4103	4135	4086	4221	4288
	46	40W5K	105	117	4827	5129	5168	5108	5276	5359
	55	48W5K	106	118	5793	6155	6202	6129	6331	6431
	62	56W5K	108	120	6758	7181	7236	7151	7386	7503
	71	64W5K	109	121	7723	8207	8269	8173	8442	8575
	79	72W5K	110	122	8689	9233	9303	9194	9497	9647
	87	80W5K	111	124	9654	10258	10336	10216	10552	10719
	94	88W5K	112	125	10620	11284	11370	11237	11607	11791
	102	96W5K	114	126	11585	12310	12404	12259	12663	12863
4K	37	32W4K	96	106	3584	3808	3837	3792	3917	3979
	46	40W4K	98	108	4480	4760	4796	4740	4896	4974
	55	48W4K	99	109	5375	5712	5755	5688	5875	5968
	62	56W4K	100	111	6271	6664	6715	6636	6855	6963
	71	64W4K	101	113	7167	7616	7674	7584	7834	7958
	79	72W4K	102	114	8063	8568	8633	8532	8813	8952
	87	80W4K	103	115	8959	9520	9592	9480	9792	9947
	94	88W4K	104	116	9855	10472	10551	10428	10772	10942
	102	96W4K	105	117	10751	11424	11511	11376	11751	11936
3K	37	32W3K	87	96	3244	3447	3473	3432	3546	3602
	46	40W3K	88	98	4055	4309	4341	4291	4432	4502
	55	48W3K	89	99	4866	5170	5210	5149	5318	5402
	62	56W3K	91	101	5677	6032	6078	6007	6205	6303
	71	64W3K	92	102	6488	6894	6946	6865	7091	7203
	79	72W3K	93	103	7299	7755	7814	7723	7977	8103
	87	80W3K	94	104	8110	8617	8683	8581	8864	9004
	94	88W3K	94	105	8920	9479	9551	9439	9750	9904
	102	96W3K	95	106	9731	10340	10419	10297	10637	10805
27K	37	32W27K	86	95	3201	3401	3427	3387	3498	3553
	46	40W27K	87	97	4001	4251	4283	4233	4373	4442
	55	48W27K	88	98	4801	5101	5140	5080	5247	5330
	62	56W27K	90	100	5601	5951	5997	5927	6122	6219
	71	64W27K	91	100	6401	6802	6853	6773	6996	7107
	79	72W27K	91	101	7201	7652	7710	7620	7871	7995
	87	80W27K	92	102	8001	8502	8567	8467	8746	8884
	94	88W27K	93	103	8802	9352	9424	9313	9620	9772
	102	96W27K	94	105	9602	10203	10280	10160	10495	10660

Capitals



PLC1 - 8 3/4" High



PLC2 - 10 13/16" High



PLC3 - 6 7/8" High



PLC4 - 7 13/16" High



PLC5 - 9 15/16" High



PLC6 - 8 1/16" High



PLC7 - 8 3/8" High



PLC8 - 11 3/8" High



PLC9 - 14 1/4" High



PLC10 - 10 1/4" High



PLC11 - 15" High

Bands & Cages



A1 - Cast Aluminum Perforated Cage



A2 - Cast Aluminum Band



A3 - Cast Aluminum Cage



A6 - Cast Aluminum Cage w/ Perforated Band



A7 - Cast Aluminum Cage w/ Flat Band



A6M - A6 Cage with Medallions*

*A1, A6, and A7 are available with Medallions. Add M to the end of the part number.

Spinnings



T1 - T101 Top Spinning



T3 - T103 Top Spinning



T4 - T104 Top Spinning

Fixture Finials



GF2 - 6"



GF3 - 6"



GF4 - 6"



GF5 (Plastic) or
GF6 (Cast) - 4"



GF7 - 4.5"



GF8 - 4"



GF9 - 4.25"



GF10 - 3.5"



GF12 - 2.75"



GF17 - 4"



GF18 - 2.75"




GF24 - 4.75"

Saratoga 2

LED Post Top

PristmaticFinish



Close up of prismatic globe.

