

Conquistador 2

LED Post Top



← Fitter section slips over 3" or 2 5/8" pole or tenon

Specifications and Features:

Radiant™ LED

- Conformal Coating LED light engine
- CCT: Standard-3000K, 4000K, & 5000K
- 2700K, Amber, LPS (1800K) Offered for Some Wattages - Consult Factory
- Static Colors Available - Contact Factory

Distribution

- Types II, III, IV, V
- Full Cutoff

Electrical

- Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz
- 0-10v Dimmable Driver
- Standard Surge Protection included (6kV line-line; 10k-V line-earth)

Controls (Optional)

- Button Eye Photo Control (PC)
- House Side Shield (H)

Housing

- Decorative Aluminum Capital Housing Choices with 3" Slip Fitter

Finish

- Super Durable Polyester Powder Coat Finish. Custom Finishes Available, Including Patinas and All RAL Colors.

Listings & Ratings

- ETL Listed to UL 1598 Standard for Wet Location.
- LED is IP66 Rated

Warranty

- 5 Year Limited Warranty

EPA: 1.9
Weight: 42 lbs (Max.)



Order Information Example:

82CON2FP60W5KU5PTHBK

82CON2						PT		
Model	Globe/Lens	Wattage	CCT	Voltage	Optics	Mounting	Options	Finish
82CON2=Conquistador 2 Post Top Radiant™	CA =Clear Acrylic FA =Frosted Acrylic WA =White Acrylic PA =Pattern Acrylic CP =Clear Polycarbonate FP =Frosted Polycarbonate WP =White Polycarbonate	10W =10w 15W =15w 20W =20w 30W =30w 40W =40w 50W =50w 60W =60w	3K =3000K 4K =4000K 5K =5000K	U =120-277V H =347/480V	2 =Type II 3 =Type III 4 =Type IV 5 =Type V	PT =Post Top	PC =Button Eye Photo Control H =House Side Shield N =None	STANDARD FINISHES BK =Black BZ =Bronze DBZ =Dark Bronze WH =White GR =Green SM =Silver Metallic GY =Light Gray TBK =Textured Black CC =Custom Color (Consult Factory)

Conquistador 2

LED Post Top



Photometric Data



8" Radiant™



6" Radiant™

RADIANT™ LED LIGHT ENGINE SPECIFICATIONS:

Lumen Output for Conquistador 2								
Wattage (Catalog Logic)	10w (10W)	15w (15W)	20w (20W)	30w (30W)	40w (40W)	50w (50W)	60w (60W)	
Radiant Size (DIA.)	6"	6"	6"	6"	8"	8"	8"	
Input Watts	10.2	14.6	20.4	30.6	40.8	51.0	56.6	
Optic	CCT	Delivered Lumens						
2 = Type II Clear, Frosted, or Ribbed Lens	3K	1,344	1,763	2,352	3,527	4,703	5,878	7,055
	4K	1,371	1,800	2,400	3,600	4,800	6,001	7,200
	5K	1,392	1,828	2,437	3,655	4,874	6,091	7,310
	BUG Rating	B0-U2-G1	B1-U2-G1	B1-U2-G1	B1-U2-G1	B1-U3-G1	B1-U3-G1	B2-U3-G2
3 = Type III Clear, Frosted, or Ribbed Lens	3K	1,342	1,760	2,348	3,521	4,695	5,869	7,043
	4K	1,369	1,797	2,396	3,595	4,792	5,991	7,188
	5K	1,390	1,825	2,433	3,649	4,866	6,081	7,298
	BUG Rating	B1-U2-G1	B1-U2-G1	B1-U2-G1	B1-U2-G1	B2-U3-G2	B2-U3-G2	B2-U3-G2
4 = Type IV Clear, Frosted, or Ribbed Lens	3K	1,312	1,721	2,296	3,443	4,591	5,739	6,887
	4K	1,339	1,758	2,343	3,515	4,686	5,858	7,029
	5K	1,359	1,784	2,379	3,569	4,758	5,947	7,136
	BUG Rating	B1-U2-G1	B1-U2-G1	B1-U2-G1	B1-U2-G1	B1-U3-G2	B2-U3-G2	B2-U3-G2
5 = Type V Clear, Frosted, or Ribbed Lens	3K	1,373	1,801	2,402	3,603	4,804	6,005	7,207
	4K	1,401	1,839	2,452	3,678	4,903	6,130	7,355
	5K	1,423	1,867	2,489	3,734	4,979	6,222	7,467
	BUG Rating	B1-U2-G1	B1-U2-G1	B2-U2-G1	B2-U2-G1	B3-U3-G1	B3-U3-G1	B3-U3-G2
5 = Type V with White-Opal Lens	3K	964	1,446	1,928	2,893	3,857	4,821	5,785
	4K	984	1,477	1,969	2,953	3,937	4,921	5,906
	5K	999	1,499	1,998	2,998	3,997	4,997	5,996
	BUG Rating	B1-U3-G1	B1-U3-G1	B1-U3-G2	B1-U4-G2	B1-U4-G2	B2-U4-G3	B2-U5-G3

Please refer to the fixture's IES file for detailed information. Subject to change.

Conquistador 2

LED Post Top



Dimensions

